

ASSEMBLY INSTRUCTION

SKU#510-463

NOTE: Please consult a qualified electrician if you are not certain of the installation.

CAUTION: Before starting the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box.

1. Pull the supply wires and house ground wire out from the outlet box and fasten mounting strap onto outlet box using 2 outlet box screws.
2. Unscrew the ring the screw collar loop. Thread the screw collar loop into nipple on the mounting strap.
3. Screw the loop down to top nipple of the fixture; Screw the upper post of the into bushing of the fixture. Make sure do not over tighten.
4. Using two pliers, twist open one link at the end of the chain. Hook it to the loop and close the link. Weave the fixture wires and ground wires up through the loop, through the chain links, through the ring, through the screw collar loop, and through the canopy. Twist open the link at the other end of the chain, hook the whole fixture to the screw collar loop and close the link.
5. Connect the wire with writing on it from the fixture to the black wire from the supply circuit. Connect the wire without writing on it (with raised ribs) from the fixture to the white wire from the supply circuit. Cover the connections using the wire connectors provided. Tie the ground wires from outlet box and fixture to the ground screw on the mounting strap.
6. Place the canopy over the nipple all the way to the ceiling and tighten the ring onto the screw collar loop until the canopy is firmly held against the ceiling.
7. Fasten the finial to the bottom nipple.
8. Place the glass shade over the socket and fasten the socket ring to the socket.
9. Install the bulbs (bulbs included).

